The PRO-TEC System One is designed to monitor and protect the trailer and its contents using a built-in accelerometer and door pins. Any movement of the trailer or the opening of a door will trigger the alarm, causing the electrical brakes to be applied, exterior siren to be sounded, and trailer running lights to flash, hindering movement and alerting anyone nearby. PRO-TEC is proud to be the only alarm company that backs their equipment with a five-year warranty.

Features include:

Five Year Warranty
Optional Cellular/Paging
(May Save on Insurance Premiums)
All Hardware Included
Easy Installation





Trailer Alarms, LLC 301 Main Plaza #241

New Braunfels, TX 78130

A Product Of





### Siren:

- Water Resistant
- •120+ dB Sound

## **Remote Transmitters:**

•Key chain remote control units arm/disarm at a range of 200 feet. (Additional remotes available)

## Brackets (3):

•Universal steel mounting bracket for pin switches.

## Super Pin Switches (3):

- Polycarbonate Shafting
- •Stainless Steel Spring
- Nickel-Plated Steel Body
- •Tin-Plated Brass QC Terminal

## (Optional)

# Cellular/Paging System:

- •Cellular notification now available through text or email. (Standard messaging rates may apply)
- Pager base unit will transmit in up to a half-mile radius when alarm or manual pager is activated.

# Optional Components



#### Part #MD-1 Interior Motion Sensor

Dual Technology with Microcontroller for False Alarm Immunity. The latest generation motion sensor uses two technologies (microwave and PIR) plus a microcontroller provides outstanding false alarm immunity without compromising detection.

Motion detector is to be used to sense motion inside the trailer, not the motion of the trailer.



### Part #KP-1 Keypad

- 100 unique 4-8 digit codes, 10,000 possible user code combinations.
- Stainless-steel face, durable and attractive.
- · Easily delete individual codes.





### Part #SM Surface Mount Switch

- Standard Gap: 1.0"
- Spacers, covers, and screws included.
- Automated gas-tight splice is soldered and epoxy covered to provide unequal electrical integrity and protection from corrosion and torque.
- White

**SPDT**:To be used as a normally open circuit for Pro-Tec System ONE.




### Part #PF38 Flush Press Fit Switch

- Completely concealed for attractive installation.
- Standard Gap: 5/8" end to end, 3/4" parallel.
- 18" leads

SPDT:To be used as a normallyopen circuit for Pro-Tec System ONE.







Part #LED-1 LED Indicator
Indicates alarm status visually from
outside of trailer

Call today for more information:

888-741-1004

Visit us on the web at:

www.ProtecSystemOne.com